



**SPECIFICATIONS**  
型号参数

型号 Model	磁棒数 Qty of magnetic bar	产量 Capacity (t/h)	磁感应强度 Magnetic induction (GS)	外形尺寸 Outline size L×W×H (mm)
YLCX-150	10	150	8000	630×490×670
YLCX-300	10	300	8000	680×660×850
YLCX-400	14	400	8000	816×748×1000

# GRAIN MAGNET SEPARATOR

## YLCX | 原粮磁选器

**YLCX** APPLICATION  
应用范围

YLCX系列原粮磁选器适用于原粮初清阶段的磁选，去除原粮中的各种尺寸、形状的铁及含铁的杂质，以避免其对后续设备造成损伤。

YLCX grain magnet separator is used to separate metal impurity from grain raw material. It could remove various sizes and shapes of iron and impurities containing iron from raw grain to avoid damage to subsequent equipment.



**YLCX** FEATURES  
特点简介

- ① 使用双开门设计，易于清理；
- ② 磁棒交错分布，保证与物料充分接触以达到更高的清理效率；
- ③ 磁棒上方设计挡板，防止物料的直接冲击导致的磨损；
- ④ 设计简洁，维护成本低。

- ① Double door design for easy cleaning.
- ② Magnetic rods are of staggered distribution to ensure full contact with materials to achieve higher efficiency.
- ③ Baffle is designed above the magnetic bar to prevent wear caused by the direct impact of materials.
- ④ Simple design and low maintenance cost.

