



SPECIFICATIONS
型号参数

型号 Model	电机转速 Shaft speed (rpm)	功率 Power (kw)	尺寸 Dimension (mm)				重量 Weight (kg)
			A	B	C	H	
ZCCD/L-100×30	1430	0.3	300	970	1090	693	220
ZCCD/L-130×30		0.7	300	1268	1390	793	300
ZCCD/L-130×50		0.7	500	1268	1390	693	280
ZCCD/L-160×30		0.7	300	1568	1690	960	570
ZCCD/L-160×50		0.7	500	1568	1690	860	550
ZCCD/L-180×50		0.7	500	1768	1890	960	720
ZCCD/L-200×50		0.7×2	500	1968	2090	1060	820

注：以上功率配置是在50Hz的电力频率情况下。
Note: Above Motor Power configuration is under 50Hz of power frequency.

VIBRO DISCHARGER

ZCCD/ZCCL | 振动出仓器

ZCCD ZCCL GOLDEN GRAIN APPLICATION 应用范围

ZCCD/ZCCL系列仓底振动器主要适用于面粉、饲料、化工、医疗等行业中粉状物料的仓底卸料。设备中心部位设有一个匀料锥体，在振动电机的作用下，卸料斗和匀料锥体随之振动，促使仓内物料缓慢而均匀地从出口流出，匀料锥体兼有防止仓内物料结拱的作用。

ZCCD/ZCCL is mainly used in flour mill, feed mill, chemical industry and medical industry for powdery materials discharging under bin bottom. It is equipped with a cone in the center. The discharge hopper and cone vibrates by driving of vibration motor, which makes the material discharged slowly and evenly from bins. And the cone is expected to prevent materials from arching.



ZCCD ZCCL GOLDEN GRAIN FEATURES 特点简介

- ① 上下段通过U型硅橡胶法兰连接，密封性好，无粉尘外溢；
- ② 定制吊杆，连接处采用进口耐磨橡胶减震，缓冲区以橡胶充实，避免吊杆与机体之间的直接磨损，寿命长，无噪音；
- ③ 振动频率稳定，可连续均匀卸料；
- ④ 采用定制小型振动电机，降低功耗；
- ⑤ 针对不同物料，电机振动幅度可调；
- ⑥ 匀料锥体杜绝结拱及积料死角；

- ① The upper and lower sections are connected by silicone rubber flange with good sealing and no leaking.
- ② It use specialized connection rod with imported wear-resistant rubber, fill with rubber completely in the buffer to avoid direct wearing between the rod and the body. Longer service life and no noise.
- ③ The vibration is stable and the material can be discharged continuously and uniformly.
- ④ Use customized small vibration motor to reduce power consumption.
- ⑤ Motor vibration amplitude can be adjusted for different materials.
- ⑥ The cone is designed to prevent material arching.

