

ZCCD




VIBRO DISCHARGER

This VIBRO DISCHARGER is a feeding device installed under the bin bottom to prevent material bridging and ensure a consistent feeding rate. Its vibration-driven design promotes smooth material flow, especially for powdery or granular substances. Different model configurations are available to suit a variety of products and processing requirements, making it a flexible solution for flour, feed, and grain milling systems.



info@g-grain.com

More details please visit www.g-grain.com and download



Model	Power (kW)	A (mm)	B (mm)	C (mm)	D (mm)	E (Number of Holes)	F (φmm)	G (mm)
ZCCD-100/30	0.25	1130	1080	300	650	20	27	1000
ZCCD-130/30	0.7	1430	1380	300	700	28	27	1300
ZCCD-130/50	0.7	1430	1380	500	700	28	27	1300
ZCCD-160/30	0.7	1732	1680	300	850	30	27	1600
ZCCD-160/50	0.7	1732	1680	500	850	30	27	1600
ZCCD-180/50	0.7	1932	1880	500	950	40	27	1800
ZCCD-200/50	0.7	2132	2080	500	1050	40	27	2000
ZCCD-160/65	0.7	1732	1680	500	850	30	27	1600
ZCCD-180/75	0.7	1932	1880	500	950	40	27	1800
ZCCD-200/75	0.7	2132	2080	500	1050	40	27	2000